CERTIFIED LAND CORNER RECORDATION				
· · · · · · · · · · · · · · · · · · ·	DESCRIPTION OF CORNER EVIDENC	E FOUND, AND ORIGINAL	RECORD (If known)	
7.12N	FOUND! NAIL SYNASHE	R FIRMLY SET	IN ASPHALT	
6 5 7 8 R60W	SET! 5/8"x 18" REBAI 0,05' BELOW SURFA BELOW			. •
	DESCRIPTION OF MONUME TO PERPETUATE THE ORIG			
	SEE THES BELOW			
SKETC	H, WITH COURSE AND DISTANCE TO A (May Sketch or Paste	ADJACENT CORNER IF DE Reproduction on Reverse		/EY.
	R.N. IN TOP OF POST	15,33	ロロロト・セ アロムモ	
	-x-x-x	43,83		\bowtie
	RM INTOP OF POST!		7.12N. R.60M, 6 5 7 8 1983 1.5.2500	
	SONN A. STEIL		fully performed or review	ved the work
done on the dia	agrammed corner as reported on this re	Signature of Surveyor	the same.	2.5.2500 Registration No.
STATE OF WYC	DMING,			
Office of Clerk	. 1	,	74	10 197
County of		5 D D	400.1	
This "corner reconnection the cross-ind	ord" was filed for record on theclex plat and is assigned page No	day ofAPR 1 , in book No	<u> </u>	_, was noted
	1. 1		County Official	
		Cross Index No.	5 T. 12N R. &	
			T R	Mer.
•			T R T R	
			T R	Mer.
			T R	Mer.
			T R	Mer.