CERTIFIED LAND CORNER RECORDATION		
DESCRIPTION OF CORNER EVIDEN	CE FOUND, AND ORIGINAL RECORD (If	known)
T. 12 N		
1	FIRMLY SET, FLUSH W.	/ CIID FANE
IR 7 14 FOUND; R" IRON PIPE IN, R.GON.		SURPACE
IW. R.60W.		·
	MENT AND ACCESSORIES ESTABLISHED IGINAL LOCATION OF THIS CORNER:	···
TO PERFEIGATE THE ON	IGHAL LOCATION OF THIS CONNEX.	
SEE THS BELOI	m and a second	
	•	
CHETCH WITH COURSE AND DISTANCE TO	ADJACENT CORNER IS DETERMINED	IN THE CHOVEY
SKETCH, WITH COURSE AND DISTANCE TO (May Sketch or Paste	Reproduction on Reverse Side.)	IN THIS SURVET.
	16	Λ
	12 7	$\Lambda$
	9	
. 10 10 10 10 10 10 10 10 10 10 10 10 10	4	
PASTURE	6	6.3
	3	
	2	Λ
	FOUND MONUMENT	_
NO TIES AYAILABLE MEAR BY	8	
	8664.2	<b>L</b> ]
	2 /2/15	70085
		( CAN 6_
	4	
	12 7 13 18	
	13 18	
I, SONN A STETH	certify that I have carefully perform	med or reviewed the work
one on the diagrammed corner as reported on this	recordation forth and approve the same	ı. <i>/</i>
	John A. Sla	15,2500
	Signature of Surveyor	Registration No.
TATE OF WYOMING,		740804
ffice of Clerk and Recorder,		170001
ounty of Garanie	APR 1 9 190#	
nis "corner record" was filed for record on the	_day of1 1 4 1304	, 19, was noted
. The Gross-Hidex Piet etter is essigned helpe 140		
	County Offic	
	Cross Index No. 6-25 T. /	2 N R. 6/N/ Mer. 6
	<b>T</b> .	K Mer.
	<del>-</del> "	R Mer.
	T T	