CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) LOCATION Corner re-established by (solar) bearing and G.L.O. distance from the Wyoming, Nebraska, Colorado monument. S-22 S-23 G.L.O. record - Retracement survey by Edwin H. Van Antwerp in 1911. S 89°59° W, 57.92 chains (sandstone 12 x 12 x 2 ins.) C.C. T.12N., R.60W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: At the corner: No monument set. Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap, as Witness Corner, from which the C.C. bears S 89°59' W, 40.00 feet distant. Accessories: 4" x 4" x 4' Redwood Post with aluminum sign set 1.5' N of W.C., scribed Wyoming on N and Colorado on S face. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) S.C. b°05'45" 206.58 REA Line Tel. Line COUNTY ROLD NO 52 (paved) WYOMING NEBRASKA Fd. G.L.O. rec. mon. 40.00' W.C. COLORADO N 89°59' E 3,822.71 1"=40" Brass cap set 6" above ground. Brass cap stamped: WYOMING T.12N. W.C. R.60W. S.22 S-23 WYO LS 519 1973 COLORADO R.L. Hudson **_certify** that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerky and Recorder, County of Maramul This "corner record" was filed for record on the cross-index plat and is assigned page No.12-60, in book No. ON E County Official

N.O-17 12-60

Cross Index No._

_ T. _

. T. .

_ T. _

... T. ..

_ T. _ _ T. _ . R. ...

_ R. __ _ R. __

_ R. _

. R. _

Photographa Germany

County clerk & Ex-Otticio Register of Deeds