# )75943

## Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date 9/6/90 Office Reference 209/

EVIDENCE FOUND: Found # 4 rebar with no cap.

NOTE: Origin UNKNOWN

GLO RECORD:

MONUMENT SET: NONE

REFERENCE POINTS SET : NO NE

Monument Inscription
LOCATION SKETCH
TIZN
RGIW

SEC 18

FOUND THE REBAR OF

FOUND PK + BOTTLE

CAP IN RR. TIE

FENCE CORNER.

SEC . 17

NOTE: LORNER WAS NOT VERIFIED, OR FILED CAL previously.

State of Wyoming Office of County Clerk

County of LARAMIE

This Certified Land Corner Recordation Certificate was filed for record on the day of \_, 19 \_\_\_, in Book No. T <u>12 ル</u>, R \_ ( ), on Alpha-Numeric coordinates and was noted on the Cross Index Plat. County Clerk 18 1 Meridian GTH P. M Section(s) Corner Type: Aliquot Corner Other Township 12 N Range 61 W Y4 COR. Page \_ Corner Name

Sheet / of /

BOOK 1293


× ± 548

## Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For <sup>1</sup>/64, <sup>1</sup>/256, <sup>1</sup>/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filled in the front of each book of certificates).

#### **Cross Index Plat**



#### State Plane Coordinates (optional)

Zone	W	WC	EC	E	feet/meters		
□ NA	D 1927		NG	/D 1929	NAD 1983	NAVD 1988	
North (Y) =				East (X) =		EL =	
Latitude					Longitude		_
Scale Factor					Geoid Height		

### Certification

1. Jettrey	B. Zewes Wyoming PLS-PE 590 certif
	ny supervision, have performed the work as described above and completed this form.
Company or Agency	INTERMOUNTAIN PROFESSIONAL SERVICES, INC.
Mading Address	1816 CENTRAL AVENUE
Street Address	
City, State, ZIP	CHEYENNE, WYOMING 82001
Telephone, FAX	PH. 307-632-3138 FAX 307-632-3194

BOOK 1293

549