Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.


Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument T12N R63 is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument. _____ Office Reference T9 1 1 **Monument Inscription** FND. 2 1/2" DIA. B. C. Found G.L.O. Brass Cap buried approximatley 1' beneath the surface of a dirt road... Other data as shown on the drawing. State of Wyoming Office of County Clerk County of LARAMIE This Certified Land Corner Recordation Certificate was filed for record on the _____ day of _, 19 ___, in Book No. T 12 N., R 63 W, on Alpha-Numeric coordinates c ~ 13 and was noted on the Cross Index Plat. County Clerk Meridian 6 th PM Section(s) Corner Type: Aliquot Comer Other Township 12 N Range 63 W Corner Name _ Sheet ____ of __

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha–numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For ¹/64. ¹/256, ¹/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

					-	
Zone	\mathbf{W}	WC	EC	E	feet/meters	
☐ NAD	1927		NG NG	VD 1929	NAD 1983	NAVD 1988
North (Y) =		<u>. </u>		East (X) =		EL =
Latitude					Longitude	
Scale Factor					Geoid Height	
				Certi	fication	
I. LARRY T.	PER	RY			, Wyomin	g PLS- 3047 certify
that I, or others u	nder my	supervi	sion, hav	e performed	the work as described	above and completed this form.
Company or Age Mailing Address Street Address City, State, ZIP Telephone, FAX				.127 Ter	82 ry Ranch Rd. e, WY 82003	- / state 1. Post 1. P
						Larry Mosern Les.
						ture, Seal, and Date
				Sheet _	of	