CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) LOCATION Found 2" x 4" x 9" Granite stone with " $\frac{1}{4}$ ", lying on top of ground, 50 feet NE (downslope) of re-established corner. S.12 S. 7 Corner re-established by single proportionate measurement. T.12N. G.L.O. record - Boulder stone, 10 x 8 x 7 R.66W., R.65W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: At the corner: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap. Accessories: Raised small rock mound south of corner monument. Left stone as memorial. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Basis of Bearing - By solar obs. φ S.C. Distances by electronic means. -N 0⁰32†15" E 2,644.47 4 cor. Not to Scale Brass cap set 6" above ground. Brass cap stamped: R.66W. T.12N. R.65W. S.12 S. 7 S.C. LS 519 1973 R.L. Hudson _certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Signature of Surveyor Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Maramul This "corner record" was filed for record on the 22 md day of . on the cross-index plat and is assigned page No. 2-66, in book No. County Official Cross Index No. _ R. _____ _ T. _

G = 1 12 -65

. R. .___ . R. _

_ R. ___ . R. _

_ R. _

T. _

Τ. T. _

T. .

282707

5 5	Book er	A. D. 19 and duly recorded	Rived day of Macca	at V. Z.Z o'clock	This instrument was	County of Laramie	
•	on page	and duly recorded	of Mass.	ckM. on	s filed for rec	**************************************	

Photographed Indexed Posted

County Clerk & Ex-Officio Register of Deeds