CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found 5" x 7" x 14" Granite stone with notches (per record). LOCATION S.12 S. 7 S.13 S.18 G.L.O. record - Boulder stone, 12 x 8 x 6 T.12N. R.66W., R.65W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap. At the corner: Raised rock mound (wall) downslope of corner monument. Accessories: Left stone as memorial. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Basis of Bearing - By solar obs. 를 cor. Distances by electronic means. N 0⁰32'15" E 2,644.46 -416 (total) S.C. Rock Mound Not to Scale S 0°17'00" W 2,632.22' Brass cap set 6" above ground. Brass cap stamped: R.66W. T.12N. R.65W. S.12^{S.}S. 7 S.13 S.18 쇼 cor∙ LS 519 1973 R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Maramil County Official Cross Index No._ R. ____

J-1 12-65

R. .

_ R. _ _ R. _

. R. .

_ R. _

. Mer.

_ T. . _ T. .

_ T. _

. T. .

. T. _

photographed indexed