## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORN	IER EVIDENCE FOUND, AND ORIGINAL RECORD (If know	
T. I. 2 N.	AND ORIGINAL RECORD (IT KNOW	<b>∀n)</b>
مام		
8 9 FOUND: GRANITE STONE	F, FIRMLY SET, PROJ. 10" 5" ABOYE GROUND PLAINLE	r
•	NOTCHES ON B. EDGE & 4 GROOVES ON E, FACE.	
R.G G W.		
DESCRIPTION		
TO PERPETUAT	OF MONUMENT AND ACCESSORIES ESTABLISHED THE ORIGINAL LOCATION OF THIS CORNER:	
	THIS CORNER:	
JEE TIES BELOW	,	
		•
SKETCH, WITH COURSE AND DIST	ANCE TO ADJACENT CORNER IF DETERMINED IN TH	HIS SURVEY
(May Sketc	ch or Paste Reproduction on Reverse Side.)	THE CONTEST
	•	
	RED-HEAD IN FENCE POST	
	2 21	$\wedge$
	3/X SHEADPOS	<u> </u>
	PER EN	Ŋ
	SIN X X X X X X X X X X X X X X X X X X X	Ц
-	20,60	
•		
		-
		•
	- · ·	
	'	
I, JOHN A. STEIL	certify that I have carefully performed	or reviewed the work
done on the diagrammed corner as reported	d on this recordation form and approve the same,	
	John A. Stal	<b>2500</b>
	Signature of Surveyor	Registration No.
STATE OF WYOMING,		649919
Office of Clerk and Recorder,		033313
County of Jarange.		
This "corner record" was filed for record on	the day of MAR 5 1982	, 19, was noted
on the cross-index plat and is assigned pag	•	, 17, WB\$ NOTEU
· ·	11. mc hitatehead	
	County Official	· · · · · · · · · · · · · · · · · · ·
	Cross Index No. 4.9 T. 12	R <i>66</i> Mer.
	<u>T</u>	R Mer.
	T	R Mer. R Mer.
•		R Mer. R Mer.
•	T	R Mer.
	T	R Mer.

eri Transport