## State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.


G.L.O. RECORD : SANDSTONE 24x11x9"

FOUND: GRANITE STONE IGX 10"x 10"

SET: 34 CAP ON 2 3/8" x 36" ALUMINUM PIPE

REF. SET: PK MAIL WITH WASHER LS # 566 IN

FENCE POSTS.



189565
LARAMIE 555,11, 6, 68
OHEYENSE, 57,
796 SEP 13, RM 10 57

MONUMENT SET

TO NI/4 GIZ SEC 10

PK NAIL WITH WASHER

NOTE: STONE BURIED

LS # 566 IN FENCEPOSTS


NEXT TO MONUMENT

Date of Field Work: 21 July 95

Office Reference:

Z831

## CROSS INDEX DIAGRAM




Firm/Agency, Address

INTERMOUNTAIN PROFESSIONAL SERVICES, INC. 5801 OSAGE AVENUE CHEYENNE WY 82001

Telephone Number: (307) 632-3138

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE



Corner Name: SEC CORN.

Section: 4 3 TIZN R 66N; 6 P.M. Cross-Index No.: E-13

BOOK 1432