

State of Wyoming Corner Record

(In compliance with the *CORNER PERPETUATION AND FILING ACT*, Wyoming Statutes, 1997, Section 33-29-140, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

G.L.O. Record: Not applicable

Found: Nothing

Set: 2 1/2" x 30" aluminum pipe with 3 1/4" aluminum cap, 28" in the ground. Set a carsonite marker post north.

Aluminum Cap Markings

T12N R67W

C 1/4 S3

1999

P.L.S. 2927

LARAMIE COUNTY CLERK
CHEYENNE, WY.


1999 JUN 21 AM 9:06

254553

Date of Field Work: April 27, 1999

Office Reference: A.V.I. Job No. 2121

CROSS INDEX DIAGRAM




Firm/Agency, Address
Paul A. Reid, P.L.S.
A.V.I., p.c.
2035 Westland Road
Cheyenne, WY 82001

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE

Telephone Number:
(307) 637-6017



Corner Name: C 1/4
SBRPEPLS/PLSW: March 1994

Section: 3 T.12N., R.67W.; 6th P.M. Cross-Index No.: C-15