

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)
Closing Cor. bet. Sec's 5 & 6, T 12 N, R 68 W

Record: Intersect 3rd corr. line N., 412 lks east of standard cor. to sec's. 31 & 32, T 13 N, R 68 W. Where I, set a blue flint stone 14"x 10"x 8" for closing cor. to sec's 5 & 6, T 12 N, R 68 W.

Found: A 18"x 6"x 5" granite stone part partially buried in a circle of rocks. Stone has 1 groove on W. face. Reset stone 10" in ground.


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Built mound of rocks on the ne side.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

031616
RECEIVED
LARAMIE COUNTY
CHEYENNE, WY.
'87 JUL 20 AM 8 35

I, Dick R. Griffin certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.


Signature of Surveyor

2785
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of LARAMIE

This "corner record" was filed for record on the 20th day of July, 1987, was noted on the cross-index plat and is assigned page No. _____, in book No. _____.


County Official

Cross Index No. <u>A-5</u>	T. <u>12 N</u>	R. <u>68 W</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.