

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)
Closing Cor. bet. Sec's 4&5 , T 12 N, R68 W

Record: Intersect 3rd corr. line at 330 links E. of standard cor. to secs. 32 & 33, T13N, R68W where I, set a boulder stone 15"x 11"x 9" for closing cor. to secs. 4 & 5, T12N, R68W.

Found: A 6"x 6"x 13" granite stone, 4 grooves on E. face & 1 groove visable on W. face. CC visable on south face. Reset stone 8" deep in ground with CC on south face.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Built mound of rocks 2' east.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

RECEIVED
LARAMIE COUNTY
CHEYENNE, WYOMING
27 JUL 20 AM 8 35

031615

I, Dick R. Griffin certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Dick R. Griffin
Signature of Surveyor

2785
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of LARAMIE

This "corner record" was filed for record on the 20th day of July, 1987, was noted on the cross-index plat and is assigned page No. _____, in book No. _____

Janet C. Whitehead
County Official

Cross Index No.	A-9	T.	12 N	R.	68 W	Mer.
_____	_____	T.	_____	R.	_____	Mer.
_____	_____	T.	_____	R.	_____	Mer.
_____	_____	T.	_____	R.	_____	Mer.
_____	_____	T.	_____	R.	_____	Mer.
_____	_____	T.	_____	R.	_____	Mer.
_____	_____	T.	_____	R.	_____	Mer.