

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

South 1/4 Cor. Sec. 6, T 12 N, R 68 W

Found: A 8"x 4"x 14" granite stone marked 1/4. Found stone lying buried with the marked face visable. I, reset stone 8" deep in ground with 1/4 on north face. A 5/8" iron pin in place on south edge of stone.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Built mound of rocks 2' east.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

RECORDED
LARAMIE COUNTY
CHIEF CLERK
27 JUL 20 AM 8 35

031614

I, Dick R. Griffin certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Dick R. Griffin
Signature of Surveyor

2785
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of LARAMIE

This "corner record" was filed for record on the 20th day of July, 1987, was noted on the cross-index plat and is assigned page No. _____, in book No. _____.

Joseph C. Whitehead
County Official

Cross Index No.	<u>E-3</u>	T.	<u>12 N</u>	R.	<u>68 W</u>	Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.