

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

West $\frac{1}{4}$ Cor., Sec.7, T 12 N, R 68 W

Record: Set boulder stone 12x10x6 for $\frac{1}{4}$ sec. cor.

Found; A 8"x 8" boulder stone marked $\frac{1}{4}$ on west face. Stone protruding 6" above ground and firmly set in ground. Scattered mound of rocks on west side.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Rebuilt mound of rocks west of stone.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

RECEIVED
LARAMIE COUNTY CLERK
CHEYENNE
JUL 20 AM 8 35

031613

I, Dick R. Griffin certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Dick R. Griffin
Signature of Surveyor

2785
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of LARAMIE

This "corner record" was filed for record on the 30th day of July, 1987, was noted on the cross-index plat and is assigned page No. _____, in book No. _____

Joseph C. Whithead
County Official

Cross Index No.	<u>G-1</u>	T.	<u>12 N</u>	R.	<u>68 W</u>	Mer.
	<u>G-25</u>	T.	<u>12 N</u>	R.	<u>69 W</u>	Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.
		T.		R.		Mer.