

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)  
Sec. Cor. common to sec's 8,9,16 & 17, T 12 N, R 68 W

Record: Set boulder stone 14"x 9"x 7" for sec. cor. to sec's 8, 9, 16 & 17.

Found: 14"x 9"x 7" boulder stone set firmly in ground inside a circle of rocks. Marks are visable on the south face.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Built a mound of rocks 3' south.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)

031618  
RECEIVED  
LARAMIE COUNTY CLERK  
CHEYENNE WYOMING  
.87 JUL 20 AM 8 35

I, Dick R. Griffin certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*Dick R. Griffin*  
Signature of Surveyor

2785  
Registration No.

STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of LARAMIE

This "corner record" was filed for record on the 20<sup>th</sup> day of July, 1987, was noted on the cross-index plat and is assigned page No. \_\_\_\_\_, in book No. \_\_\_\_\_

*James C. Whitcomb*  
County Official  
Cross Index No. J-9 T. 12 N R. 68 W Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.