|                     | CERTIFIED LAND CORNER RECORDATION   |
|---------------------|---|
|                     | DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)                |
| T.13 N.             |   |
| RGIW, RGOW,         | FOUND! 2" IRON PIPE WIBRASS CAP, 20" BELOW  |
| 36 3/               | SURFACE MARKED AS SHOWN BELOW.  |
| 00                  | SET! 5/6"× 18" REBAR ON TOP OF BRASS CAP, 2"<br>BELOW SURFACE                       |
| •                   |   |
|                     |   |
|                     | DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED                                 |
|                     | TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:                                 |
|                     |   |
|                     | IEE TIES BELOW  |
|                     | SEE THE BELOTT  |
|                     |   |
|                     |   |
| SKETCH,             | WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.           |
|                     | (May Sketch or Paste Reproduction on Reverse Side.)                                 |
|                     |   |
|                     | $\wedge$  |
|                     | P. H. IN FENCE POST   |
|                     | x x x x x x x x x x x x x x x x x x x   |
|                     | 28.95 CHISELED "X" AT END OF CMP  |
|                     |   |
|                     | 8.6 408.73 26.90  |
|                     | CC FG. MONUMENT   |
|                     | CO, RD. #203 1-14.0   |
|                     |   |
|                     | 730.70  |
|                     | x-x-x-x-x-x   |
|                     | SET 1/2" REBAR  |
|                     | 7.13M<br>RG/W 536 RGOW,531  |
|                     | RG/W 536 RGOW53)  |
|                     | C C   |
|                     |   |
|                     |   |
|                     |   |
|                     |   |
| I,                  | Certify that I have carefully performed or reviewed the work                        |
| done on the diag    | rammed corner as reported on this recordation form and approve the same.            |
|                     | A. Seil 1,8,2500  |
|                     | Signature of Surveyor Registration No.  |
| STATE OF WYOM       | ING.  |
| Office of Clerk a   |   |
| County of           | aramie.   |
|                     | 5DD + 0 100 Å   |
| This "corner record | I" was filed for record on theday ofAPR 1 2 1984, 19, was noted                     |
| on the cross-index  | plat and is assigned page No, in book No  |
|                     | Court Official  |
|                     | County Official  County Official  County Official  County Official  County Official |
|                     | Cross Index No. $\frac{Z-25}{Z-1}$ T. $\frac{13N}{1}$ R. $\frac{6/N}{60N}$ Mer. 6   |
|                     | T R Mer.  |
| •                   | T R Mer.  |
|                     | T R Mer.<br>T R Mer.  |
|                     | T R Mer.  |
|                     | 7-1 13-60   |

2-1 13-60