State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

FOUND: GRANITE STONE 18'x 9'x 6

SET: 34 ALUMINUM CAP ON ALUMINUM PIPE STAMPED AS SHOWN

REFERENCES SET: P.K. NAIL AND WASHER STAMPED LS 546


GLO RECORD: GRANITE BOULDER 18x 11x 7"

NOTE: STONE BURIED NEXT TO MONUMENT

WASHER STAMPED LS 546
18x 11x 7"

LUMENT

LARAMIE OGUHTI CLERK CHEYENNE, WY. '96 SEP 13 RM 10 57



,P.K. WITH WASHER STAMPED LS BLL IN PENCE POST


R 64 W

Date of Field Work: _

July 17, 1995 Office Reference:

<u> 2823</u>

CDOCC MIDEV DIACDAN



Firm/Agency, Address

INTERMOUNTAIN PROFESSIONAL SERVICES, INC. 5801 OSAGE AVENUE CHEYENNE WY 82001

Telephone Number: (307) 632-3138

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE

See 1996

Corner Name: 4 Cor 4.3 Section: TISN RG4W; L P.M. Cross-Index No.: C-13

1