

T.13N. R.6W.

1/4 Cor S.2  
S.11

RECEIVED  
LARAMIE COUNTY  
CHEYENNE, WY.

'94 MAR 25 PM 2 11  
138866

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

RECORD: EDWIN JAMES & ALFRED M. ROGERS, U.S. DEPUTY SURVEYORS, JUNE, 1891  
RECORD OF MONUMENT IS NOT KNOWN.

FOUND: BROKEN SANDSTONE WITH FAINT MARKINGS. STONE APPEARED BROKEN OFF AT TOP AND IN NEED OF RE-MONUMENTATION.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

SET: USING DONALD M. HOPKINS TIES AND MONUMENTS I VERIFIED THE CORNER POSITION BY FINDING THE BROKEN SANDSTONE. SET A 2" AL. CAP AS EXHIBITED ON A 9/8" X 2 1/2" REBAR. BURIED ORIGINAL STONE ALONGSIDE.

S.S.S.  
T.13N. R.6W.  
1/4 S.2  
S.11  
1993  
252927

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)

SEE RECORD OF SURVEY DATED 10-29-1993 FOR CHARLIE CATHART BY STEIN SURVEYING SERVICES FOR TIES TO ADJACENT CORNERS AND CORNERS SET.

I, Paul A. Reid certify that I have carefully examined the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

Registration No.



STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of \_\_\_\_\_

This "corner record" was filed for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_, was noted on the cross-index plat and is assigned page No. \_\_\_\_\_, in book No. \_\_\_\_\_.

Y: Cor 2  
11

County Official			
Cross Index No. <u>E-19</u>	T. <u>13N.</u>	R. <u>6W. 6th</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

BOOK 1369

0531