

T.13N. R.64W.  
1/4 Cor. S.11/S.12

RECORDED  
LARAMIE COUNTY  
CHEYENNE, WY.

'94 MAR 25 PM 2 10

CERTIFIED LAND CORNER RECORDATION

138864

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

RECORD: EDWIN JAMES & ALFRED M. ROGERS, UNDER JOINT CONTRACT, U.S. DEUTY SURVEYORS,  
JUNE, 1871.

38.00 CHAINS LEASE VALLEY BEARS E & W.

40.00 CHAINS SET A SAND STONE <sup>17"</sup> 8" X 7" FOR 1/4 SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

A SEARCH WAS MADE FOR THE DONALD M. HOPKINS MONUMENT PER C.L.C.R.  
FORM DATED 2 SEPTEMBER 1987, CROSS INDEX NO. G-21 T.13N. R.64W.

MONUMENT WAS NOT FOUND. FOUND A BROKEN MARKED SANDSTONE @ FENCE INTER-  
SECTION OF FENCES EXTENDING NORTH, SOUTH & EAST. SET A 2" ALU CAP.  
@ THE BASE OF THE FENCE INTERSECTION AND BURIED STONE ALONGSIDE.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)

SEE RECORD OF SURVEY DATED 10-29-1993  
FOR CHARLIE CATHCART BY STEEL SURVEYING SERVICES  
FOR TIES TO ADJACENT FOUND OR SET CORNERS  
AND SECTION BREAKDOWN.

I, PAUL A. REID certify that I have carefully performed ~~the~~ the work  
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

Registration No.

STATE OF WYOMING,

Office of Clerk and Recorder,

County of \_\_\_\_\_

This "corner record" was filed for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_, was noted  
on the cross-index plat and is assigned page No. \_\_\_\_\_, in book No. \_\_\_\_\_.

County Official

Cross Index No. <u>G-21</u>	T. <u>13N.</u>	R. <u>64W. 6<sup>th</sup></u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

BOOK 1369

0529