

T.13N. R.6W.
1/4 5.11
5.14

138861
RECEIVED
LARAMIE COUNTY
CHEYENNE, WY.

'94 MAR 25 PM 2 10

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

RECORD: EDWIN JAMES & ALFRED M. ROBERTS, UNDER JOINT CONTRACT, U.S. DEPUTY SURVEYOR,
JUNE, 1871 - MONUMENT RECORDED UNKNOWN BY THIS SURVEYOR.
LARAMIE COUNTY ROAD RECORDS - BOOK NO. 11 PAGES 42-43 INDICATES A FOUND STONE
AND WITNESS CORNERS SET 40' N.T.S.
FOUND: A SET WELL MARKED STONE 40.00' N. OF CORNER SET. STONE WAS MARKED C.R. W.C.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

SET: A MARKED 2" AL. CAP ON A 5/8" X 24" REBAR 0.5' BELOW GRADED
COUNTY ROAD @ 40.00' SOUTH OF FD. "W.C.C.R." STONE. DATED 2 SEPT. 1987
CAP WAS MARKED S.S.S. D.M. HOPKINS CORNER PER C.L.C. R. AT-19 T.13N.
R.6W. WAS FOUND DISTURBED APRIL, 20'
WEST OF TRUE CORNER. R
1/4 -11
14
1993
LS 2927

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

SEE RECORD OF SURVEY DATED 10-29-1993
FOR CHARLIE CATHCART BY STEEL SURVEYING SERVICES
FOR TIES TO ADJACENT FOUND OR SET CORNERS
AND SECTION BREAKDOWN.

I, PAUL A. REID certify that I have carefully performed and approved the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of _____

This "corner record" was filed for record on the _____ day of _____, 19____, was noted
on the cross-index plat and is assigned page No. _____, in book No. _____.

Cross Index No.	County Official		Mer.
	T. 13N.	R. 6W. 6P.	
J-19			Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.