Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

G.L.O. RELORD: GRANITE STONE 8"X6"X2"

SET SB"XZY" REAR WITH Z" ALUMINUM CAP MARKED AS SHOWN.

LESET FROM REFERENCES OF PREVIOUS FORM,
STONE WAS DISTURSED.

CARAMIE COUNTY CLERK CHEYENNE, WY.

'95 DEC 13 PM 3 55

PK NAIL IN GATE POST

P. P. K NAIL IN GATE POST

SSS 7.13 N. R. GGW. 1/4 3 10 0, 1995 5 59

Date of Field Work: 3-7-95

_Office Reference:

95060

CROSS INDEX DIAGRAM

Firm/Agency, Address

STEIL SURVEYING SERVICES

1102 WEST 19th STREET

CHEYENNE WY 82001

Telephone Number: (307) 634-7273

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE

Date / NING

ROOK 1413

Corner Name: NORTH 14 SBRPEPLS/PLSW: March 1994

Section: 10 T/3N R 66W; 6TN P.M. Cross-Index No.: E-15

0505