CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Location

14 s.9 = s.10 T13N R66W 6th P.M.

Found Brass Cap

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: 3¼" Brass Cap on 2¼" Iron Pipe, ½' above ground.

Marked - E.P. Kelley, P.E. & L.S. 638

s.9 + s.10 1969

T. _____ R. ____ Mer.

SKETCH, WITH COURSE AND DISTANCE TO ADJA	CENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Repr	oduction on Reverse Side.)
	70/ -
	9710
	11
	↓ ○ 60 d Nail above ground on
	West side of fence corner
	Post.
	SCALE 1''=
Dirt Trail	
•	
	4
,	.38
	55
Center of	
Manhala Q 12	
30" Tree	
30.77	
60 d Nail 2' above grour	ad
on North side of Power	
Pole	
William D. Promon	August 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
WITH all U. Brallan	certify that I have carefully performed or reviewed the work
done on the diagrammed corner as reported on this recor	
566	* \$1) illian D. Brana #566
	Signature of Surveyor Registration No.
CANDA	
STATE OF WYOMING,	
Office of Clerk and Recorder,	568601
Office of Clerk and Recorder,	00000T
County of Janamie	
This "corner record" was filed for record on theday	of
This "corner record was filed for record on file day	in book No
on the cross-index plat and is assigned page No,	
	County Official
	County Official
	Cross Index No T R Mer.
	Cross Index No
	T R Mer.

6-130 13-66