Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

found monument.

Field Date 3-6-89 Office Reference 2-8792

G.L.O. Record: Unknown

Found no evidence of previous monumentation.

Set 5/8"x 24" long rebar with 2" aluminum cap north of found WHD R/W monument.

Monument Inscription

E /4 cor.

P north of

PIRE HYDRANT ON ALUM. CAP of 1983

LS 2500

STREE HYDRANT ON LS 2500

PIRE H

RECEIVED
LARAMIE COUNTY
CHEYENNE, WY.

State Wyoming
Office of County Clerk
County of <u>Laramie</u>

This	Certified	Land	Corner	Recordation	Cert	ificate	was	filed	for	record	on	the	day	of
			_, 19	_, in Book N	o. T	13N	,	R 66	5W	, on A	Alph	a-Numeric	coordin	ates
	J-11			on the Cross I							-			

 County Clerk

 Corner Type:
 Section(s)
 9, 16
 Meridian
 6th P.M.

 X Aliquot Corner
 Other

 Corner Name
 Quarter
 Township
 13N
 Range
 66W
 Page


Sheet ____ of ___

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For ¹/64, ¹/256, ¹/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone W	WC EC	E	feet/meters	
NAD 1927	□N	GVD 1929	☐ NAD 1983	NAVD 1988
North (Y) =		East $(X) =$		EL = 2
Latitude			Longitude	
Scale Factor			Geoid Height	
		Certif	ication	:
l, <u>John A. Steil</u>			. Wyoming	PLS- E 2500 certify
that I, or others under n	ny supervision, ha	ive performed t	he work as described a	bove and completed this form.
Company or Agency	Stell Survey	ng Services		
Mailing Address	P.O. Box 2073			oto sessional Land Sunta
Street Address	200 E. 8th Av			1055 Oct.
City, State, ZIP	Cheyenne, WY	82003		OLO TOHN A. S. C.
Telephone, FAX	307-634-7273			- / O P 2560 0 2 /
				Date 372 PO
			· .	7.7
		Sheet	Signatu_of	re, Seal, and Date
				

BOOK 1284

1597