State of Wyoming Corner Record
(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors.) Reverse side of this form may be used if more space is needed.


Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

G.L.O. Record: Set Granite Boulder $16 \times 12 \times 10$ for corner to Sections 29, 30, 31 & 32, August 28, 1870, Henry G. Hay, U.S. Deputy Surveyor.


Subsequent Record: Certified Land Corner Recordation Form filed May 15, 1989 by Mr. Larry T. Perry, Wyoming P.L.S. 3047, indicating a found Wagon Bolt set as section corner Sept. 1968 and of record in the Laramie County Engineer's office files.

Found: 2 1/2" square headed bolt on a 1" x 18" threaded end stem.

Set: 2 1/2" x 30" Galvanized Iron Pipe with a 3 1/4" Brass Cap, 26 inches in the ground. Brass Cap was stamped as noted below. Placed the found bolt inside the 2 1/2" iron pipe as a memorial. Set a 6' steel fence post witness 1 ' north.



Date of Field Work: August 7, 1995ffice Reference: Job No. 2-1918.95



SBRPEPLS/PLSW:March 1994 (CLCR_SJA)

Corner Name

Firm/Agency, Address

PREPARED BY:

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE

2035 Westland Road Cheyenne, WY 8200 of Struct AP (307) 637-6017



1407

1025

66W. 6th
P.M. Cross-Index No.: