State of Wyoming Corner Record

(In compliance with the <u>CORNER PERPETUATION AND FILING ACT</u>, Wyoming Statutes, 1997, Section 33-29-140, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)


Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

G.L.O. Record: U.S. Deputy Surveyor, Henry G. Hay, September 4, 1870; Set Granite Boulder 17 x 9 x 9 for 1/4 Sec Cor.


Found: A fairly well set 17" x 9" x 6" granite type stone with a 1/4 on the West face, 9" out of the ground.

Set: At the corner point I set a $2\frac{1}{2}$ " x 30" aluminum pipe with a $3\frac{1}{4}$ " aluminum cap, 26" in the ground. A No.5 x 24" rebar for magnetic reference was set inside the pipe. Buried the original stone adjacent and south of the remonumented corner point as a memorial. The remains of a broken off concrete monument well set and with the remains of a brass stem bears N89°38'W, 3.14' from this remonumented corner.



Date of Field Work: Dec. 2, 1998 Office Reference: A.V.I. Job No. 2-2100

CROSS INDEX DIAGRAM



Firm/Agency, Address

Paul A. Reid, A.V.I.p.c.

2035 Westland Road

Cheyenne, WY 82001

Telephone Number:

(307)-637-6017

This corner record was prepared by me or under my direction and supervision.



Corner Name: W 1/4 Section: 4 T 13N. R 67W. 6thP.M. Cross-Index No.: C-9

BOOK 1504