


Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.



Field Date _____ Office Reference _____

Monument Inscription

7 FOUND STONE &
ALUM. CAP LS 3881
309°43'43"E
2612.88
TRAIL
18

State of Wyoming

Office of County Clerk

County of Laramie

This Certified Land Corner Recordation Certificate was filed for record on the 17th day of Oct, 1991, in Book No. T 13N, R 67W, on Alpha-Numeric coordinates J-3 and was noted on the Cross Index Plat.

Janet C. Whithead
County Clerk

Corner Type:

Aliquot Corner

Other

Section(s) 7, 18

Meridian 6th P.M.

Corner Name 1/4 COR.

Township 13N.

Range 67W Page _____

Sheet _____ of _____

RECEIVED
 LARAMIE COUNTY
 CHEYENNE, WY.

OCT 18 PM 1 25


090854

BOOK 1310

25

Sheet _____ of _____

Signature, Seal, and Date
Donald M. Hopkins



Company or Agency: Don Hopkins
 Mailing Address: Box 6106
 Street Address: Cheyenne, WY 82003
 City, State, ZIP: 632-4763
 Telephone, FAX:

I, Donald M. Hopkins, Wyoming PLS/PE 558 certify that I, or others under my supervision, have performed the work as described above and completed this form.

Certification

North (Y) = _____ East (X) = _____
 Latitude _____ Longitude _____
 Scale Factor _____ Geoid Height _____
 Zone NAD 1927 NGVD 1929 NAD 1983 NAVD 1988
 W WC EC E
 feet/meters

State Plane Coordinates (optional)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A	6	5	4	3	2	1																			
B																									
C	6	5	4	3	2	1																			
D																									
E																									
F	7	6	5	4	3	2	1																		
G																									
H																									
J																									
K	8	7	6	5	4	3	2	1																	
L																									
M																									
N																									
O	19	18	17	16	15	14	13																		
P																									
Q																									
R																									
S																									
T	30	29	28	27	26	25																			
U																									
V																									
W																									
X	31	32	33	34	35	36																			
Y																									
Z																									

Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/4, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Directions for using the Cross Index Plat