
Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date _____ Office Reference _____



Monument Inscription

589°42'43'E

26/2.88

FOUND MARKED

STENE IN FENCE

State of Wyoming

County of ARAMIE		county Clerk	
County of	County of	LARAMI	/E

						41
This Certified	Land Corner	Recordation C , in Book No.	ertificate was	filed for reco	ord on the	day of
WE1_	, 19 <i>Z</i>	Z, in Book No.	1 /3// ,	R G/W	on Alpha-Num	eric coordinates
<u>ک- لـ</u>	_ and was note	d on the Cross Ind	ex Plat.	Fruit C	White	
				,	unty Clerk	
Corner Type: Aliquot Cor	ner 🔲	Section(Other	s) 7,8,14,	<i>18</i> Meridia	n 6 th	orincija)
Corner Name	Tec. Co.	rner Townshi	p <u>13N</u>	Range _	67 W	Page


Sheet ____ of ____

Directions for using the **Cross Index Plat**

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies,

Closing corners will be indexed under the township in which they control ownership. For $\frac{1}{64}$, $\frac{1}{256}$, $\frac{1}{1024}$ and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	WC EC E	ieet/ineters	
NAD 1927	☐ NGVD 1929	NAD 1983	NAVD 1988
North (Y) =	East (``() =		EL =
Latitude		Longitude	
Scale Factor		Geoid Height	
	Certifi	cation	
that I, or others under my	N. HOPKINS supervision, have performed the Sox POPKINS & C BOX POPKINS	ie work as described abov	e and completed this form.
Street Address City, State, ZIP Telephone, FAX	Cheyenne, WY 632-4763	82003	O'Nessyl, m.

7

Signature, Seal, and Date

Sheet ____ of