## **Wyoming Certified Land Corner Recordation Certificate**

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.


Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In	T. 13	3 N.
the circle to the right, show monument inscription. If monument		,
is determined lost or obliterated restate the GLO or BLM		\
original field note record; describe or show the procedure	13	18
used to reestablish the corner and all data as above for a		1
found monument.		
Field Date Office Reference	24	19
		/
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0	
79 00	R.68W.	P. 67 W.
10 4	W.	P. 6.
2648.4		
3 1	Monument	inscription
<u> </u>		
2		
\$ 89° 50'31"W 2625,42'		
2625,42		
HIGHWAY BURIE R-O-W. SET 2 OTTO ROAD		
X X X FOUND	MARKEDS	TONE
HIGHWAY BURIE	D STON	
R-O-W. SET 2	4. PREE.	BLASS CAP
		, .
OTTO ROAD		
<b>}</b>		
State of Wyoming		
Office of County Clerk		
County of Xammee		
This Cortified Land Corner Decordation Cartificate was filed	for magned on	the 15th day of
This Certified Land Corner Recordation Certificate was filed, 19 9/, in Book No. T 12 N., R 67-	or tecord on	a Numeric coordinates
and was noted on the Cross Index Plat.	on ruph	a runserie coordinates
		71
Star	ut C. J.	helth f
	Counfy C	lerk
Communication 13 19 16 54	لو بر دورون	# D41
Corner Type: Section(s) 13/18/19, 24	ivierigian_ <u>@</u>	- 1001
<del></del>		10.11-
Corner Name SEC. COR. Township 13N.	Range <u>/ 4 6/</u> -	68W Page
Sheet of		

## Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For <sup>1</sup>/64, <sup>1</sup>/256, <sup>1</sup>/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

## **Cross Index Plat**



## **State Plane Coordinates (optional)**

Zone	VV	WC	EC	E	feet/meters		
NA NA	D 1927		NGV	/D 1929	NAD 1983	NAVD 1988	
North (Y) =				East (X) =		EL =	
Latitude					Longitude		_
Scale Factor					Geoid Height		

	Scale Factor	Geoid Height	
		Certification	
	that I, or others under a Company or Agency	ny supervision, have performed the work as described above and completed this form	ertify n.
	Mailing Address Street Address	130× 6106	
5	City, State, ZIP Telephone, FAX	Chayenne wy 82003	
			<i>X</i>
<u>a</u>	25	8/5	-91
100	03080	Davadd M Hopkins	<u>)                                    </u>
'91		Sheet of	

CHEYETS WY

**8001. 131**0