Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.
Field Date Office Reference \
38.
& G
Monument Inscription
$\frac{2}{3}$
17 16
N 89°40' 27" W
NE9°40'27'W 2617.01' MARKED STONE 20 21
2617.01' MARKED STONE
20 21
*
State of Wyoming
Office of County Clerk
County of Aramel
This Certified Land Corner Recordation Certificate was filed for record on the day o, 19 2/, in Book No. T /3 N/, R (4742), on Alpha-Numeric coordinates
and was noted on the Cross Index Plat.
County Clerk
Corner Type: Section(s) 17,16 to 21 Meridian 6th P, M
Corner Type: Section(s) 17,16 20 21 Meridian 6 th P, M, Aliquot Corner Other
— · · — — · · · · · · · · · · · · · · ·
Corner Name SEC. COD. Township /3N. Range 67 W. Page
Sheet /_ of _/_

BOOK 1310


24

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For ¹/64, ¹/256, ¹/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	W	WC	EC	E	feet/meters	
NAI NAI	1927		□NGV	/D 1929	□ NAD 1983	NAVD 1988
North (Y) =				East $(X) =$		EL =
Latitude					Longitude	
Scale Factor					Geoid Height	

Certification								
		work as described above and completed this form.						
090853		Omald M Don Sins Signature, Seal and Date						

Sheet ____ of ___

BOOK 1310 -

23