Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.


Describe below, or show in sketch a evidence found. Include condition and and ties. Describe any maintenance or the circle to the right, show monument is determined lost or obliterated, repriginal field note record; describe used to reestablish the corner and found monument. Field Date Office Reference.	A type of monument, accessories rehabilitation performed. In at inscription. If monument estate the GLO or BLM or show the procedure all data as above for a	er 1. 13 N. 24 19
	8 W 7 W	R.68W. R.67W
9	¥0	Monument Inscription
24 d	FOUND IT IRON PI SET 2'5" PIPE !	PE BRASS CAP
Office of County Clerk County of		
• •		./
	Book No. T /3//, R _4	d for record on the day of day of life on Alpha-Numeric coordinates
\mathcal{P} and was noted on the	ie Closs fildex Flat.	truck C h Internet County Clerk
Corner Type: Aliquot Corner Other	Section(s) 24, b	Meridian 6 th P.M.
Corner Name 14 COR	Township 13 N	Range <i>E.</i> 67-68 W Page
		-
	Sheet of	

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies,

Closing corners will be indexed under the township in which they control ownership. For $\frac{1}{64}$, $\frac{1}{256}$, $\frac{1}{1024}$ and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	\mathbf{W}	WC	EC	E	feet/meters	
[] N	AD 1927		NGV	VD 1929	NAD 1983	NAVD 1988
North $(Y) =$				East $(X) =$		EL =
Latitude					Longitude	
Scale Factor					Geoid Height	

Certification

1. LONALL	M. HOPKINS	, Wyoming PLS/PE _	558	cei
that I, or others under m	y supervision, have performed the wor	k as described above and co	ompleted this t	orm.
Company or Agency	dm hopkins & go	SCC.	Market	
Mailing Address	BOX 6106		7.30%	
Street Address				
City, State, ZIP	Chayenne, Wy 8.	2003	-	
Telephone, FAX	682-4763		1.5	

Signature, Seal, and Date

certify

Sheet ___ of _