RECEIVED LARAMIE COUNTY

	CERTIFIED LAND	CORNER RECORDATION	CHE'	YENNE.	. ₩Y.	
S.28 S.33 .13N. R.67W. 6th P.M.	DESCRIPTION OF CORNER EVIDENCE Found granite stone 6" x 8"	FOUND, AND ORIGINAL RECOR	D (If khenny))	9 Ar	า 9	 10
	G.L.O. Record: Granite bould Thomas, Deputy Surveyors, Se		y Henry C. Ha	y & Jol	nn B	•
	DESCRIPTION OF MONUMEN	IT AND ACCESSORIES ESTABLIS	SHED	. 		_
t the corner:	TO PERPETUATE THE ORIGINAL Not remonumented.	NAL LOCATION OF THIS CORI	NER:			
.ccessories :	See ties below.					
SKETCH,	. WITH COURSE AND DISTANCE TO AI (May Sketch or Paste R	DJACENT CORNER IF DETERMINATION OF REVERSE Side.)	NED IN THIS SUR	VEY.		
	. ,	•				
1 528 4 533 STONE	90°-00'00" Z6 Z3 . 10	28 27 ALUMINUM CAP 33 34				
I, <u>John</u> done on the dia	A. Steil grammed corner as reported on this red	certify that I have carefully produced the cordation form and approve the signature of Surveyor		ewed the	2500)
STATE OF MYOU	MINIC					-
STATE OF WYO! Office of Clerk						
County of						
This "corner reco	rd" was filed for record on thed ex plat and is assigned page No	ay of _, in book No	, 19	, was	note	ed
			nty Official			- -
		Cross Index No. V-11	T R T R T R T R T R		Me Me Me Me	r. r. r. r.
			T R T R			