


**CERTIFIED LAND CORNER RECORDATION**

<p>LOCATION</p> <p align="center"><math>\frac{1}{4}</math></p> <p>S. 6 S. 5</p> <p>T.13N., R.68W.</p> <p>6th P.M.</p>	<p>DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)</p> <p>Found granite stone, 6" x 8" with "<math>\frac{1}{4}</math>" chiseled on west face. Stone planted and in good condition.</p> <p>G.L.O. record - Granite Boulder, 16 x 11 x 6, Henry G. Hay, 1870.</p>
---	--

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

None

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)



R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work corner as reported on this recordation form and approve the same.

R.L. Hudson  
Signature of Surveyor

Wyoming L.S. No. 519  
Registration No.

STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of Sarassee

This "corner record" was filed for record on the 13th day of September, 1942, was noted on the cross-index plat and is assigned page No. 13-68, in book No. ONE

J. B. Hillman  
County Official

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____