CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION

Found granite boulder, $5" \times 8" \times 16"$ with "1" chiseled on west face, in place.

S. 2 S. 1


G.L.O. record - Granite Boulder, $16 \times 8 \times 5$ (1870)

T.13N., R.69W. 6th P.M.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

None

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)



done on the diagrammed corner as reported o	Comy mai i nave carerony	certify that I have carefully performed or reviewed the work ordation form and approve the same.	
	Signature of Surveyor	Wyoming L.S. No. 519 Registration No	
STATE OF WYOMING,			
Office of Clerk and Recorder,			
County of <u>Hasamil</u>			
This "corner record" was filed for record on the on the cross-index plat and is assigned page N	29th day of	19 <u>73</u> , was noted	

County Official Cross Index No. _ T. _ . R. _ _ R. ____ . R. _ _ T. _ _ R. _

_ R. _

C-21 13-69

Photographed Nudexed V Poeted The State of Wyoming SS
County of Laramie

This instrument was filled for record

at 29 delock M. on the
A. D. 19. 23 delock Mais duly recorded in

ose wo

The Clerk & Ex-Officio Register of Deeds