

State of Wyoming Corner Record

(In compliance with the **CORNER PERPETUATION AND FILING ACT**, Wyoming Statutes, 1997 Section 33-29-140 et. seq., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.


G.L.O. RECORD:

VA 15°25' E

From corner of sections 18, 19, 13, 24
north along east boundary of section
13 40.00 chains. Set granite
boulder 18x10x5 for $\frac{1}{4}$ section corner.

AT THE CORNER:


Found a 3 $\frac{1}{4}$ " aluminum cap
in fence stamped as shown.
Also found two 1.5" aluminum caps
17' north and 17.8' east stamped RP.



Date of Field Work:

Office Reference: GRAHAM

Cross Index Plat



Firm/Agency, Address



Western R&D, Ltd.
5809 Yellowstone Rd., Suite B
Cheyenne, Wyoming 82009

This corner record was prepared
by me or under my direction
and supervision.

SEAL & SIGNATURE

Telephone Number: (307) 632-5656

● Found monument, left in place



Corner Name: East 1/4 corner Section 13, T 13 N, R 69 W, 6th P.M.

Cross-Index No.: L-25

County: Laramie Wyoming

SBRPEPLS/PLSW: March 1994; PLSW January 1998



RECORDED 3/17/2008 AT 2:00 PM REC# 495592 BK# 2050 PG# 594
DEBRA K. LATHROP, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF 1