

# State of Wyoming Corner Record

(In compliance with the **CORNER PERPETUATION AND FILING ACT**, Wyoming Statutes, 1997 Section 33-29-140 et. seq., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.


**G.L.O. RECORD:**

VA.15°47'E  
From corner to sections 23,24,25,26 north along the line between sections 23,24 40.00 chains. Set granite boulder 22x8x6 for 1/4 section corner.

**AT THE CORNER:**  
FOUND NOTHING  
PLACED A 2.5" ALUMINUM CAP ON A 5/8" X 24" REBAR FLUSH WITH THE GROUND STAMPED AS SHOWN.

Set two 2" aluminum caps stamped RP on 5/8" x 24" rebar, 20' north and 20' east.


**CORNER WAS RESET BY SINGLE PROPORTION METHOD**



Date of Field Work: 10/08/07

Office Reference: GRAHAM

**Cross Index Plat**



Firm/Agency, Address


Western R&D, Ltd.  
5809 Yellowstone Rd., Suite B  
Cheyenne, Wyoming 82009

This corner record was prepared by me or under my direction and supervision.

**SEAL & SIGNATURE**

Telephone Number: (307) 632-5656

● Denotes Monument Set



Corner Name West Quarter Corner Section 24, T 13 N, R 69 W, 6th P.M.

Cross-Index No.: P-21

County: Laramie Wyoming

SBRPEPLS/PLSW: March 1994; PLSW January 1998