

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Brass Cap On Iron Pipe Surrounded By Rocks Appiox. 6" Above Ground. Found 2 Reference Markers Marked C.P. #7 & C.P.#8. Section Corner Measured 85' From CP#7 & 63' From C.P.#8 Reference Markers Were Alum. Caps On Steel Rods.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

See attached!
[Handwritten mark]

I, Gerald H. Mathew certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Gerald H. Mathew Wyoming Hwy. Dept.
Signature of Surveyor Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of Sarasie

#697241

This "corner record" was filed for record on the 5 day of May, 1983, was noted on the cross-index plat and is assigned page No. _____, in book No. _____.

Jan C. Whitehead
County Official
Cross Index No. _____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____

N-13 T14N R60W

CROSS INDEX PLAT

T. 14 N R. 60 W MER.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6					5				4				3				2				1		
D																									
E																									
F																									
G		7					8				9				10				11				12		
H																									
J																									
K																									
L		18					17				16				15				14				13		
M																									
N																									
O																									
P		19					20				21				22				23				24		
Q																									
R																									
S																									
T		30					29				28				27				26				25		
U																									
V																									
W																									
X		31					32				33				34				35				36		
Y																									
Z																									

LEGEND



Corners filed under this cross index plat.



Certificates filed in adjoining township as indicated by solid quadrant(s).

Each corner certificate is identified by an alphabetical-numerical coordinate number which is derived from the system shown on the above township diagram. For example, the quarter-corner between Sections 5 and 6 is identified as Corner C-5.

Corners such as meander corners or subdivision corners which are not located at intersecting lines on the above diagram will be identified by reference to the nearest applicable coordinate lines, thus:
AB-1; M-1-2; VW-19-20.

Corners common to adjoining townships will be identified by coordinates of the townships in which the certificates are to be filed.

Within each township record, the certificates will be filed in alphabetical-numerical sequence.