## **State of Wyoming Corner Record**

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1997 Section 33-29-140 et. seq., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey).

**Original Record:** 

(James Rogers - 1871) Set sand stone 17x10x7 for corner to sections 34, 35, 2 & 3

**Evidence Found:** 

No evidence of original stone. I evaluated fences in all directions from approximate corner. I

determined the railroad tie fence corner to be the best evidence of the corner.


Perpetuation:

On the west side of railroad tie fence corner, I set a 5/8" x 24" rebar with 2 1/2" diameter aluminum cap marked as shown below. Cap is set flush with ground and situated as shown

below.



Monument Inscription



**NE S34** 2 1/2" ALUM. CAP "LS11268" -GATE 5.34 THIS CORNER 5.34 SET 2 1/2" ALUM. CAP "LS11268" | *S.35 S.33* T. 15N. N89**'**49'52 5304.89 T. 14N. SW S34 2 1/2" ALUM, CAP "I S11268"

Date of Field Work: 05-02-2019 Office Reference: Book 48 Pg 6

