CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) LOCATION Corner established by this survey. E 1/16 S. 7 S.18 T.14N., R.61W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap for corner. Raised a rock mound, 2' x 2' x 2' high, 2.5 feet north of corner. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Rock mound ½ cor. N 89°50'30" W S 89⁰59'30" E 1/16 cor. (solar) (solar) 1,317.02 1,317.03 Brass cap set 6" above prairie surface. Brass cap stamped: E 1/16 S. 7 S.18 LS 519 1972 R.L. Hudson _certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Larami This "corner record" was filed for record on the 2 th day of on the cross-index plat and is assigned page No. 14-61, in boof County Official Cross Index No. _ T. _

__ T. ____

_ T. __

_ T. ____ _ T. ____ _ R. ____ Mer.

_ R. __

_ R. _ _ R. _

__ R. ____ __ R. ____

J-4 14-61