Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BEM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

EVIDENCE FOUND: #5 Rebar Origin UNKNOWN

GLO RECORD:

MONUMENT SET:

REFERENCE POINTS SET: See Sketch P.K., + Washers - PLS 5910 Monument Inscription
LOCATION SKETCH

Sec 13
THN R63W

Sec 13
THN R63W

P.K. + Washer
IN R.R. Tie
North Side Gate

P.K. + Washer
IN R.R. Tie
South Side Gate

The Reserve Post.

North Side Gate


P.K. + Washer
IN R.R. Tie
South Side Gate

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha—numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	w	WC	EC	E	feet/meters		
NAD 1927			□NGV	D 1929	☐ NAD 1983	NAVD 1968	
North (Y) =				East (X) =		EL =	_
Latitude					Longitude		
Scale Factor					Geoid Height		

Certification

1. Jettrey & Z	wyoming PLS-BE 59/0 certify supervision, have performed the work as described above and completed this form.
	my supervision, have performed the work as described above and completed this form.
Company or Agency	INTERMOUNTAIN PROFESSIONAL SERVICES, INC.
Mailing Address	1816 CENTRAL AVENUE
Street Address	
City, State, ZIP	CHEYENNE, WYOMING 82001
Telephone, FAX	PH. 307-632-3138 FAX 307-632-3194

١