# **Wyoming Certified Land Corner Recordation Certificate**

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date 11/90 Office Reference 2200

EVIDENCE FOUND: 11/2" Alum CAP

LS 519 + Reference

Points

Monument Inscription

GLO RECORD:

MONUMENT SET:

CHEYENNE, WY.
791 JAN 23 AM 9

REFERENCE POINTS SET:


| OCATION     | SKETCH   |                             |                               | 1 2 2 K                  | <u></u>  |                         |
|-------------|--|-----------------------------|-------------------------------|--------------------------|--|-------------------------|
| A           |  | Fd, RebAr<br>CAP, Ne<br>Tie | w/Plashic<br>v1 to RR         | 324                      | 1  |                         |
| 1           |  | Tie                         | ,                             | 13 18                    | *  |                         |
| 1           | County R   | Cond                        |                               | 7                        | <del>*************************************</del>     | <del></del>             |
| //          | County R<br># 212                                  | •                           |                               | - 6 E                    | <u> </u>   |                         |
|             |  | <del></del>                 | <del></del>                   | × see see                | X Esika Wille  | masher                  |
|             |  | ν,                          |                               | 74 19<br>R R             | 60D spike W/W<br>PELS 1615<br>* IN RR TIE            | ,,,,,                   |
|             | te of Wyoming<br>ce of County Cler                 |                             |                               | *64 163                  | * IN RR Tie  |                         |
| Cou         | nty of   | <u> </u>                    |                               | ,,                       |  |                         |
| This        | Certified Land                                     | Corner Recor, 19, in I      | dation Certific<br>Book No. T | ate was filed 14 N , R G | for record on the $_{-3}\mathcal{W}$ , on Alpha-Nume | day of eric coordinates |
|             |  | was noted on the            |                               | at.                      | and C Whis   |                         |
| •           |  |                             | ,                             | 13   18                  | County Clerk   |                         |
| $\boxtimes$ | ner Type:<br>Aliquot Corner<br>ner Name <u>Suu</u> | Other                       | Section(s)                    | 4 4                      | Meridian   |                         |
|             |  |                             | Township/                     | 4N_                      | Range <u>63W</u>                                     | Page                    |
|             |  |                             | Sheet _/                      | of                       |  | , ·                     |
|             |  |                             |                               |                          |  |                         |

# Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

## **Cross Index Plat**



### **State Plane Coordinates (optional)**

| Zone          | W      | WC | EC   | E          | feet/meters  |           |
|---------------|--------|----|------|------------|--------------|-----------|
| ≥ □ NA        | D 1927 |    | □NGV | /D 1929    | NAD 1983     | NAVD 1988 |
| North (Y) = _ |        |    |      | East (X) = |              | EL =      |
| Latitude      |        |    |      |            | Longitude    |           |
| Scale Factor  |        |    |      |            | Geoid Height |           |

### Certification

| 1. Jeffrey        | B, Soves                                  |
|-------------------|---|
| ·                 | INTERMOUNTAIN PROFESSIONAL SERVICES, INC. |
| Company or Agency |   |
| Mailing Address   | 1816 CENTRAL AVENUE                       |
| Street Address    |   |
| City, State, ZIP  | CHEYENNE, WYOMING 82001                   |
| Telephone, FAX    | PH. 307-632-3138 FAX 307-632-3194         |

Signature Seet and Date

BOOK 12 98