Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corne evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.	TI5N 39 R64W R63WP S36 S31 33 33 33 33 33 33 33 33 33 33 33 33 3
Field Date 10-4-89 Office Reference 89084	PM PM
G.L.O. Record: limestone 20"x 12"x 4".	1989 1
Found no evidence of previous monumentation.	Monument Inscription
Set 5/8"x 24" rebar with 2" aluminum cap down 0.5' one foot west of centerline of N-S gravel road, 35' west of fence south, 43' east of fence N-S, on line with fence E-W, position established from tie to Hills—PK IN POWER dale Plat; distance from U.P.R.R. plans and G.L.O. distance, averaged position of above. State of Wyoming Office of County Clerk County of Laramie This Certified Land Corner Recordation Certificate was filed—	TO TECORD ON the day of
	County Clerk
Corner Type: Section(s) $\underline{1,6,31,36}$ $\underline{\times}$ Aliquot Corner Other	Meridian 6th P.M.
Corner Name Section Township 14N	Range 63W Page
Sheet of	•


BOOK 1284

Directions for using the **Cross Index Plat**

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (focal systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	W	WC	EC	E	feet/meters	
☐ NAE	1927		□NGV	/D 1929	☐ NAD 1983	NAVD 1988
North (Y) =				East (X) =	:	EL =
Latitude					Longitude	
Scale Factor _					Geoid Height	

Certification								
1John A. Steil		. Wyor	ning PLS-RE- 2500	certify				
that I, or others under n Company or Agency Mailing Address	ny supervision, have perform Steil Surveying Service P.O. Box 2073	ned the work as describ	bed above and completed the	nis form.				
Street Address City, State, ZIP	200 E. 8th Ave. Cheyenne, WY 82003		Quotes sional	A. STEIT BO				
Telephone, FAX	307-634-7273			500				
	te.	**************************************	WYOM	ING				

Signature, Seal, and Date

Sheet ____ of