(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors.) Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

- 1. Original G.L.O. Field Notes: Township boundary, p. 116; Subdivision, p. 33.
- 2. Corner Record form by Glen L. Roberts, P.E./P.L.S. 347, recorded in the Laramie County Clerk's Office.
- 3. Corner Record form by S. Dennis Dawson, P.L.S. 555. recorded in the Laramie County Clerk's Office 30 November 1994 at 12:07 p.m.

Corner was recovered in good condition. The information contained in Reference No. 3 is accurate. This report is to provide latest date of recovery and the information stamped on the aluminum cap established by Mr. Dawson.

R64W

LARAMIE COUNTY CLERI CHEYENNE, WY.

Date of Field Work: 14 June 1997

Office Reference:

CROSS INDEX DIAGRAM 1-20

Firm/Agency, Address

This corner record was prepared by me or under my direction and supervision.

PREPARED BY: Dr. Herbert W. Stoughton & SIGNATURE

Geodetic Engineer 2821 Carey Avenue Cheyenne, Wyoming 82001

(307) 632-7460

31,32 15N

10 11 12 13 14 15 16 BOOK 1 SARIEPE /PLSW: March 1994 (CLCR\_SJA) ROOK 1 14NR64 W; 6th\_P.M. Cross-Index No