

State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors.)


Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

References:

1. Original G.L.O. Field Notes: Township Boundary, p. 116.
2. Corner Record form by S. Dennis Dawson, P.L.S. 555, recorded in the Laramie County Clerk's Office 18 November 1994 at 4:27 p.m.

The original corner was recovered in good condition. The rebar witness corner was recovered, but the aluminum survey cap (Dawson's) had been removed. Set a new aluminum cap on rebar, as shown below. The witness corner (WC) is 3.48 feet east of the center of the original corner (rock).



Stamping

204706
 LARAMIE COUNTY CLERK
 CHEYENNE, WY.
 '97 JUN 20 AM 10 20

BOOK 1453

0844

Date of Field Work: 15 June 1997 Office Reference: _____

CROSS INDEX DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C																									
D																									
E																									
F																									
G																									
H																									
I																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

Firm/Agency, Address

PREPARED BY:

Dr. Herbert W. Stoughton
 Geodetic Engineer
 2821 Carey Avenue
 Cheyenne, Wyoming 82001
 (307) 632-7460

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE

32, 33 15N

A-9

Corner Name: Not Applicable Section: 5, 4 T 14N R64W ; 6th P.M. Cross-Index No.:
 SDRPEPLS/PLSN: March 1994 (CLCP SJA)