## CERTIFIED LAND CORNER RECORDATION

LOCATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

S. 6 S. 5 T.14N., R.66W. 6th P.M.

Found 6" dia. x 30" long concrete monument with brass cap, 6" above ground surface.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

- 1. Relocated monument with brass cap, 6" below ground surface.
- 2. R.P. No. 1 A 5/8" dia. x 24" long rebar with Surv KAP bears N 1° E (mag.), 49.80 feet distant.

  R.P. No. 2 A 5/8" dia. x 24" long rebar with Surv KAP bears S 1° W (mag.), 44.83 feet distant.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

Brass cap stamped: PELS 538 T 14 N S 6 \frac{1}{4} S 5 R 66 W

1969

QR.P. No. 1 --- N 1° E 49.80' 1"=40"

O R.P. No. 2 R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk and Recorder,

County of Laramie

on the cross-index plat and is assigned page No. 4-66, in book No. DNE

> County Official \_ T. . Cross Index No.-\_\_\_\_ T. \_\_\_\_ \_\_\_\_ R. \_\_\_\_ Mer. \_ R. \_\_\_\_

\_ R. \_\_\_\_ \_\_\_\_ R. \_\_\_\_ Mer. \_ T. \_

\_ T. \_\_\_ \_\_\_\_ R. \_\_\_\_ Mer. \_ T. \_ \_ R. \_\_\_\_ Mer.

C-5 14-66

R.L. Hudson This instrument was filed for record at 2.22 o'clock M. on the A. D. 19. 22 and this recorded in Book on the control of the co County Clerk & Ex-Officio Register of Deeds