

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION No evidence found. Corner re-established by single proportionate measurement.

 1/4 S.14
 1/4 S.23 Underground telephone line in vicinity of corner position.

T.14N., R.66W.
6th P.M.


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a 1 1/2" dia. x 30" long iron pipe with brass cap.

Accessories: Raised a small rock mound, 2 feet N of corner monument.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

Basis of Bearing - By solar observation.



Brass cap set 4" above ground.

Brass cap stamped:

T.14N. R.66W.

1/4 S.14
1/4 S.23

LS 519 1973

I, R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson
Signature of Surveyor

Wyoming L.S. No. 519
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of Saramie

This "corner record" was filed for record on the 29th day of May, 1973, was noted on the cross-index plat and is assigned page No. 14-66, in book No. ONE.

John B. Hillman
County Official

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____

289684

Photographed.....
Indexed.....
Posted..... *DM*

The State of Wyoming } SS
County of Laramie }

This instrument was filed for record
at 9:54 o'clock A.M. on the
29 day of May
A. D. 1923 and duly recorded in
Book of page

John A. [Signature]

Clerk & Ex-Officio Register of Deeds
Cherise August Deputy