Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument. Field Date 9-2-89 Office Reference 89020	
1989	2
GLO Record: Unknown	
Found no evidence of previous monumentation. Set 5/8" x 24" rebar with 2"aluminun cap flush in DellRange Blvd. 4' north of centerline of Dell Range and on N-S centerline of Whitney Road. Corner position set from adjacent subdiivisions and we stone State of Wyoming Office of County Clerk County of Laramie Monument Inscription X TOP OF YOUR STONE WE STONE WE STONE A PRIN POWER ME PRIN POWER ME POWER ME A PRIN POWER ME POWER ME POWER ME A PRIN POWER ME A PRIN POWER ME POWER ME A PRIN POWER	
This Certified Land Corner Recordation Certificate was filed for record on the day of, 19, in Book No. T, R, on Alpha–Numeric coordinates and was noted on the Cross Index Plat.	
County Clerk	
Corner Type: Section(s) 23,24,25,26 Meridian 6th P.M.	
Corner Name Section Township 14N Range 66W Page	
Sheet of	


BOOK 1284

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

	State I I	ane Coordii	nates (optional)	
Zone W NAD 1927	WC EC □NGV	E fee D 1929	et/meters	
-				NAVD 1988
North (Y) =		East (X) =		EL =
Latitude			Longitude	
Scale Factor			Geoid Height	
•		Certifica	·tion	
		Cerunca	เนงก	
I, John A. Steil that I, or others under the	my supervision, have i	performed the v	, Wyoming PL	S=== 2500 certify re and completed this form.
company of Agency	ocerr ourveying	Services	work as described above	e and completed this form.
Mailing Address	P.O.Box 2073			and the same of th
Street Address	200 E.8th Ave.		-	cional Land
City, State, ZIP	Cheyenne, WY 820	03		Quolesional Lang Store
Telephone, FAX	307-634-7273			10 10 10 S.
				## 2550 2550 2550 2550 2550 2550 2550 2550
				Date
		Sheet of	Signature	, Seal, and Date