


Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.


Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date 15 June 90 Office Reference _____



'91 JUN 10 12 59
 LARAMIE COUNTY
 CHEYENNE, WY.
 0799907

*Fnd. conc. monument
w/ brass cap
(WHD type)
"X" mark on brass cap*



*Reference
Iron Pipe set by
Bill Braman (PLS 566)
corner record used*

State of Wyoming
Office of County Clerk
County of _____

This Certified Land Corner Recordation Certificate was filed for record on the _____ day of 2-13, 19 ____, in Book No. T _____, R _____, on Alpha-Numeric coordinates A-13 and was noted on the Cross Index Plat.


Corner Type: <input checked="" type="checkbox"/> Aliquot Corner <input type="checkbox"/> Other		Section(s) <u>33 34</u> <u>4 3</u>	Meridian <u>6th</u>
Corner Name <u>Section</u>	Township <u>T14N</u> <u>T13N</u>	Range <u>R68W</u>	Page _____
Sheet _____ of _____			

**Directions for using the
Cross Index Plat**

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone W WC EC E feet/meters

NAD 1927 NGVD 1929 NAD 1983 NAVD 1988

North (Y) = _____ East (X) = _____ EL = _____

Latitude _____ Longitude _____

Scale Factor _____ Geoid Height _____

Certification

I, Peter J. Hutchison, Wyoming PLS-PE 707 certify that I, or others under my supervision, have performed the work as described above and completed this form.


Company or Agency Jack Noblitt and Associates

Mailing Address 1920 Thomas Ave Suite 620

Street Address _____

City, State, ZIP Cheyenne Wyoming 82001

Telephone, FAX 307-634-9064



Signature, Seal, and Date

Sheet ____ of ____