

049153


RECEIVED
LARAMIE COUNTY
CHEYENNE, WY.

CERTIFIED LAND CORNER RECORDATION

'88 SEP 22 PM 3 32

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

T14N R68W



Found GRANITE STONE 1/4 MARK ON WEST FACE. STONE LIEING
down PARTIALLY buried.
ALO RECORD - GRANITE BOWIDER 14"X8"6" (1870)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


REMOVED STONE SET 2" X 24" GALVANIZED PIPE WITH SURV. CAP.
MAKE 1/4 RESET ROCK UPSIDE DOWN ON SOUTH SIDE OF PIPE

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)



25'

Sec. 3



Sec. 10

Field Survey
Sept, 1988

SEE OTHER SIDE FOR
CORNER TIES

I, Edward C. Fry certify that I have carefully performed or reviewed the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Edward C. Fry
Signature of Surveyor

PE/LS 662
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of Laramie

This "corner record" was filed for record on the 22 day of September, 1988, was noted
on the cross-index plat and is assigned page No. 618, in book No. 1305.

Janet C. Whitehead
County Official
Cross Index No. _____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____
_____ T. _____ R. _____ Mer. _____

N 1/4 Gr.
Sec. 6

North

270° 10' 53"

7931.99'
G.L.O. 7920.0'

358° 34' 40"
5345.22'
G.L.O. 5313.0'

Sec. 4

2644.00' | 2644.00'
G.L.O. 2640.0' | G.L.O. 2640.0'

269° 50' 25"

G.L.O. 2619.9' | G.L.O. 2619.9'
2619.56 | 2619.56

G.L.O. 5303.8'
5312.88'
179° 05' 46"

Sec. 3

5287.99'
G.L.O. 5280.0'

179° 36' 23"
10577.03'
G.L.O. 10,560.0'

16 | 15
21 | 22

90° 26' 44" | 90° 11' 24"
G.L.O. 2633.4' | G.L.O. 2633.9'
2633.43 | 2630.27'

G.L.O. 5289.9'
5325.15'
179° 21' 38"

Field Survey
Sept. 1988