

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION Found fine-grained granite stone, 6" x 8" with "1/4" chiseled on north face.
 Stone planted and in good condition.
 1/4 S.19
 1/4 S.30 G.L.O. record - Granite Boulder, 12 x 10 x 8, Henry G. Hay, 1870.
 T.14N., R.68W.
 6th P.M.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a 1 1/2" dia. x 30" long iron pipe with brass cap.
 Accessories: Set a fence post, 3 feet NE'ly.
 Left stone as memorial.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
 (May Sketch or Paste Reproduction on Reverse Side.)


1/4 cor. ● □ Post



Brass cap set 6" above ground.

Brass cap stamped:

T.14N. R.68W.
 1/4 S.19
 1/4 S.30
 LS 519 1972



R.L. Hudson certify that I have carefully performed or reviewed the work on the indicated corner as reported on this recordation form and approve the same.

R.L. Hudson
 Signature of Surveyor

Wyoming L.S. No. 519
 Registration No.

STATE OF WYOMING,
 Office of Clerk and Recorder,
 County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-68, in book No. ONE

John B. Hillman
 County Official

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____

Photographed.....

Indexed X

Posted X

The State of Wyoming }
County of Laramie } SS

This instrument was filed for record
at 1:57 o'clock P M. on the

6th day of September
A. D. 19 2013 and duly recorded in

Book on page

John B. Williams

County Clerk & Ex-Officio Register of Deeds
By _____, Deputy