

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

LOCATION

Found slate stone, 4" x 10" x 15" with  $\frac{1}{4}$ " chiseled on north face. Stone was found in place.

$\frac{1}{4}$  S.31  
S. 6

G.L.O. record - Granite Boulder, 4 x 10 x 15, 1870.

T.14N., R.68W.  
T.13N., R.68W.  
6th P.M.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a  $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.  
Accessories: Set a fence post, 3 feet NE'ly.  
Left stone as memorial.


SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)



Brass cap set 6" above ground.

Brass cap stamped:

T.14N. R.68W.  
 $\frac{1}{4}$  S.31  
S. 6  
T.13N.  
LS 519 1972



R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work at the corner as reported on this recordation form and approve the same.

R.L. Hudson  
Signature of Surveyor

Wyoming L.S. No. 519  
Registration No.

STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-68, in book No. ONE

John B. Hillman  
County Official

Cross Index No. <u>13</u>	T. <u>68</u>	R. <u>6</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

Photographed.....

Indexed X

Posted X

The State of Wyoming }  
County of Taramie } SS

This instrument was filed for record  
at 1:37 o'clock P. M. on the  
6th day of September  
A. D. 19 22 and duly recorded in  
Book ..... on page .....

*John B. Williams*

County Clerk & Ex-Officio Register of Deeds  
By \_\_\_\_\_ Deputy